

Building Safety Department CITY OF ROCHESTER, MINNESOTA

EGRESS WINDOW REQUIREMENTS

No <u>clear opening height</u> dimension may be less than <u>24"</u>.

No <u>clear opening width</u> dimension may be less than <u>20"</u>.

Specification for egress windows installed before April 11, 1983 require:

- 1. Distance from the floor to the finished sill to be no more than 48".
- 2. Window must have a clear openable area of at least 720 square inches.

Specifications for egress windows installed after April 11, 1983 require:

- 1. Distance from the floor to the finished sill to be no more than 44".
- 2. Window must have a clear openable area of at least 820 square inches.

When new and/or replacement windows are being installed into an existing structure, they must meet the new requirements for sill height and clear openable area.

TYPICAL EXAMPLES OF THE REQUIRED DIMENSIONS OF WINDOWS THAT MEET THE MINIMUM REQUIREMENTS:

Installed	before Apr	il 11. 198

Installed after April 11, 1983

WID ⁻	TH	HEIGHT	WIDTH	HEIGHT
20	X	36	20 X	41
21	Χ	34 ½	21 X	39 ¼
22	Χ	33	22 X	37 ½
23	Χ	31 ½	23 X	35 ¾
24	Χ	30	24 X	34 1/4
25	Χ	29	25 X	33
26	Χ	27 ¾	26 X	31 ¾
27	Χ	27	27 X	30 ½
28	Χ	26	28 X	29 ½
29	X	25	29 ½ X	28
30	X	24	30 X	27 ½
			31 ½ X	26 1/4
			33 X	25
			34 X	24 1/4

Building Safety Shared/Housing Forms & Handouts/EGRESS WINDOW REQUIREMENTS

Aug 2002